

Jangro Limited James House Worsley Road Farnworth Bolton BL4 9NL

Tel. 0845 458 5223

# **PRODUCT SAFETY DATA SHEET**

 IDENTIFICATION OF PREPARATION AND THE SUPPLIER

 Trade Name:
 JANGRO LUXURY WAX FURNITURE POLISH

 Supplier:
 Jangro Limited, as above

# 2 <u>COMPOSITION / INFORMATION ON INGREDIENTS</u>

Ingredient Name	EINECS No.	CAS No.	% Range	Symbol	Risk Phrase
White Spirit		64742-82-1	10-30%	Xn, N	10, 51/53, 65, 66
Hydrocarbon Propellant	649-202-00-6	68476-85-7	10-30%	Fx	12

The full text for all R-phases are shown in section 16.

COMPOSITION COMMENTS: Aerosol propelled by liquefied petroleum gas.

#### 3 HAZARDS IDENTIFICATION

Extremely flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 4 FIRST AID MEASURES

Eyes:	Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes.
	Get medical attention if any discomfort continues.
Skin:	Wash skin thoroughly with soap and water. Use suitable lotion to moisturize skin.
Ingestion:	Rinse mouth thoroughly. Get medical attention if any discomfort continues.
Inhalation	If inhalation of vapours causes irritation or drowsiness, remove to fresh air.

#### 5 FIRE FIGHTING MEASURES

· · · · · · · · · · · · · · · · · · ·	
Extinguishing Media:	Fire can be extinguished using: powder, foam or CO2
Fire Fighting Procedures:	Breathing apparatus should be worn if exposure to fumes is likely. Use water to keep fire exposed
	containers cool and disperse vapours.
Explosion Hazards:	Possible risk of can rupture when exposed to fire/ high temps. Contents of aerosol will add to fuelling of fire. Solvent vapours may form explosive mixtures with air.

# 6 ACCIDENTAL RELEASE MEASURES

Spillage Cleanup Methods: Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb material from ruptured or leaking containers onto an inert - materials. Transfer to suitable container for subsequent disposal.

7	HANDLING AND STORAGE
Usage:	Keep away from heat, sparks and open flames. Avoid spilling, skin and eye contact. Caution. Pressurised
	container. Do not expose to temperatures exceeding 50°C do not puncture or incinerate even when
	empty. Do not spray onto naked flames or incandescent materials.
Storage:	Store at moderate temperatures in dry, well ventilated area.

	ROLS / PERSONAL PROTE		
	CAS No STD 64742-82-1	LT EXP (8 hrs) 100 ppm	ST EXP (15 min) 125 ppm
Protective Gloves: Eye Protection:	Chemical resistant gloves Wear approved chemical	s required for prolong	ged or repeated contact. re eye exposure is reasonably probable.
9 <u>PHYSICAL AND CH</u> Physical Form:	HEMICAL PROPERTIES Aerosol		
9 <u>STABILITY AND RE</u> Stable: Conditions to Avoid: Materials	ACTIVITY Normally Stable Avoid heat, flames and of	ther sources of ignition	on.
11 <u>TOXICOLOGICAL I</u> Inhalation: Ingestion: Skin: Eyes:		outh, respiratory trac cause skin dryness o	•
12 <u>ECOLOGICAL INFO</u>			a term adverse effects in the aquatic environme

Environmental Hazards: Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

13 <u>DISPOSAL CONSIDERATIONS</u> Disposal Methods: Do not pur

Do not puncture or incinerate even when empty. Dispose of in accordance with local authority requirements.

14 <u>TRANSPORT INFORMATION</u> Label for Conveyance:



Road:	n/a
UN No:	1950
Hazard Class (ADR):	Class 2: Gases; Compressed, liquefied or dissolved under pressure
ADR ITEN No:	5°C CEFIC TEC (R) No: 20G53
Rail:	n/a
Sea:	n/a
UN Sea:	1950
Air:	n/a
UN Air	1950

# 15 REGULATORY INFORMATION

Label for Supply:



EXTEMELY FLAMMABLE

Risk Phrases:	R-12	Extremely Flammable
	R52/53	Harmful to aquatic organisms may cause long term adverse effects in the aquatic environment.
Safety Phrases:	S-16	Keep away from sources of ignition – No smoking.
	S-2	Keep out of reach of children
	S-35	This material and its container must be disposed of in a safe way.
	S-51	Use only in well ventilated areas.
	S-61	Avoid release to the environment. Refer to special instructions/ Safety Data Sheets.
	S-9	Keep container in a well ventilated place.

## 16 OTHER INFORMATION

This information is based on our present state of knowledge and is intended to describe our products from the point of view of the safety requirements. However, the information is provided without any warrantee, express or implied regarding its correctness.

R-PHASES (Full Text)	R-10 R-12 R-51/53	Flammable Extremely flammable Toxic to aquatic organism, may cause long term adverse effects in the aquatic
	R-65 R-66	environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.