



Jangro Limited  
James House  
Worsley Road  
Farnworth  
Bolton  
BL4 9NL

Tel. 0845 458 5223

## PRODUCT SAFETY DATA SHEET

### 1 IDENTIFICATION OF PREPARATION AND THE SUPPLIER

Trade Name: JANGRO STAINLESS STEEL CLEANER  
Supplier: Jangro Limited, as above

### 2 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	EINECS No.	CAS No.	% Range	Symbol	Risk Phrase
Aliphatic Hydrocarbon		64741-65-7	5-10%	Xn	10,65,66
Hydrocarbon Propellant	649-202-00-6	68476-85-7	10-30%	Fx	12

The full text for all R-phases are shown in section 16.

COMPOSITION COMMENTS: Aerosol propelled by liquefied petroleum gas.

### 3 HAZARDS IDENTIFICATION

Extremely flammable

### 4 FIRST AID MEASURES

Eyes: Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention if any discomfort continues.  
Skin: Wash off with water.  
Ingestion: Not relevant.  
Inhalation: Provide rest, warmth and fresh air.

### 5 FIRE FIGHTING MEASURES

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.  
Fire Fighting Procedures: Use water to keep fire exposed containers cool and disperse vapours.  
Explosion Hazards: Possible risk of can rupture when exposed to fire/ high temps. Contents of aerosol will add to fuelling of fire.

### 6 ACCIDENTAL RELEASE MEASURES

Spillage Cleanup Methods: Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb with inert, damp, noncombustible materials, then flush area with water.

### 7 HANDLING AND STORAGE

Usage: Keep away from heat, sparks and open flames. Avoid spilling, skin and eye contact. Caution. Pressurised container. Do not expose to temperatures exceeding 50°C do not puncture or incinerate even when empty. Do not spray onto naked flames or incandescent materials.  
Storage: Store in a cool dry place away from all sources of heat including direct sunlight.

**8** EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>INGREDIENT NAME</b>	<b>CAS No</b>	<b>STD</b>	<b>LT EXP (8 hrs)</b>	<b>ST EXP (15 min)</b>
Odourless Kerosene	64741-65-1	OES	1200 mg/m <sup>3</sup>	3600mg/m <sup>3</sup> R

INGREDIENT COMMENTS: OES = Occupational Exposure Standard

Protective Equipment:



Ventilation:	No specific ventilation requirements noted, expect this product must not be used in a confined space without good ventilation.
Protective Gloves:	Chemical resistant gloves required for prolonged or repeated contact.
Eye Protection:	Not normally required if used as directed

**9** PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Aerosol

**10** TABILITY AND REACTIVITY

Stable:	Normally Stable
Conditions to Avoid:	Avoid heat, flames and other sources of ignition.
Materials	

**11** TOXICOLOGICAL INFORMATION

Inhalation:	High concentrations of vapour may cause dizziness, nausea and headaches.
Ingestion:	May cause irritation of mouth, respiratory tract and intestinal system.
Skin:	Repeated exposure may cause skin dryness or cracking.
Eyes:	May cause mild irritation or discomfort.

**12** ECOLOGICAL INFORMATION

Environmental Hazards: Not classified as dangerous to the environment.

**13** DISPOSAL CONSIDERATIONS

Disposal Methods: Do not puncture or incinerate even when empty. Dispose of in accordance with local authority requirements.

**14** TRANSPORT INFORMATION

Label for Conveyance:



Road:	n/a
UN No:	1950
Hazard Class (ADR):	Class 2: Gases; Compressed, liquefied or dissolved under pressure
Rail:	n/a
Sea:	n/a
UN Sea:	1950
Air:	n/a
UN Air	1950

15 REGULATORY INFORMATION

Label for Supply:

**EXTREMELY FLAMMABLE**

Risk Phrases:	R-12	Extremely Flammable
Safety Phrases:	S-16	Keep away from sources of ignition – No smoking.
	S-35	This material and its container must be disposed of in a safe way.
	S-51	Use only in well ventilated areas.
	S-9	Keep container in a well ventilated place.

16 OTHER INFORMATION

This information is based on our present state of knowledge and is intended to describe our products from the point of view of the safety requirements. However, the information is provided without any warranty, express or implied regarding its correctness.

R-PHASES (Full Text)	R-10	Flammable
	R-12	Extremely flammable
	R-65	Harmful: may cause lung damage if swallowed
	R-66	Repeated exposure may cause skin dryness or cracking.